

Water tanks



- Small folded size
- Extremely sturdy material
- Capacity of 500 – 5,000 l (17.6 – 176 cu. ft.)

www.vetter.de/vetter_emergency/en/Rescue+Products/Collection+and+Storage+of+HazMat/Water+tanks.html

Space- saving storage of fresh and contaminated water.

Need to store large volumes of water, contaminated extinguishing water? That's no problem with Vetter's self-erecting flexible water tanks. Collect and store contaminated water after accidents, storms or fires. Vetter water tanks can hold up to one hundred times their folded volume.

Closed water tanks (GWT)



Reinforced PVC gives the closed water tanks maximum stability. You can also opt to have corner brackets fitted to the tanks for safe transportation by truck - even of filled tanks. An opening on the top side of the tank serves as a vent or for refilling.

Emergency Pneumatics

Technical data

Resistant to temperatures between - 30 °C and + 70 °C (- 22 °F and + 158 °F)

Product	Art. no.	Diameter (bottom) m / inch	Diameter (opening) m / inch	Dimensions (L x W, empty) m / inch	Height m / inch	Weight, approx. kg / lbs	Folded size cm / inch	Folded size m ³ / cu.ft.	Art. no. for cover Text /
OWT 1,000	1510010300	1,76 69,3	0,7 27,6		0,8 31,5	12,0 26,5	70 x 45 x 45 27,6 x 17,7 x 17,7		
OWT 3,000	1510010400	2,64 103,9	1,4 55,9		0,9 35,4	21,00 46,3	115 x 64 x 33 45,3 x 25,2 x 13		
OWT 5,000	1510010500	3,04 119,7	2 78,7		1 39,4	27,0 59,5	115 x 64 x 33 45,3 x 25,2 x 13		
GWT 500	1510008300			1,5 x 1,2 59,1 x 47,2	0,3 13,8	9 19,8	70 x 45 x 45 27,6 x 17,7 x 17,7	0,14 4,9	
GWT 1,000	1510008400			2,1 x 1,5 82,7 x 59,1	0,45 17,7	12,0 26,5	70 x 45 x 45 27,6 x 17,7 x 17,7	0,14 4,9	
GWT 3,000	1510008600			3,4 x 2,3 133,9 x 90,6	0,5 19,7	23,0 50,1	70 x 45 x 45 27,6 x 17,7 x 17,7	0,14 4,9	
GWT 5,000	1510008700			3,5 x 3,1 137,8 x 122,1	0,6 23,6	30,0 66,1	115 x 64 x 33 42,3 x 21,2 x 13	0,24 8,5	

Accessories



In operation...

- Storage and transportation of liquids
- Removal of contaminated extinguishing water



Good reasons...

- Self-erecting without support frame
- Ready to deploy in seconds
- No accessories required
- Very stable and sturdy



Guaranteed quality:

- Made from strong, durable PVC
- Anodised 2" aluminium flange
- Shock-resistant PVC ball valve

Please contact us directly should you have any further questions concerning this product.

Sales

Phone.: +49 (0) 22 52 / 30 08-0

Fax: +49 (0) 22 52 / 30 08-590

E- Mail: vetter.info@idexcorp.com

Or find the nearest dealer under:

[www.vetter.de/ support/ haendler](http://www.vetter.de/support/haendler)
