

# Universal tents



- Immediately ready to use
- Extensive standard features
- Useable area 12 m<sup>2</sup> to 40 m<sup>2</sup> (130 to 430 sq. ft.)
- 20 m<sup>2</sup> (216 sq. ft.) set up in just 1 minute



[www.vetter.de/vetter\\_emergency/en/Rescue+Products/Pneumatic+tents+and+showers/Universal+tents.html](http://www.vetter.de/vetter_emergency/en/Rescue+Products/Pneumatic+tents+and+showers/Universal+tents.html)

## Your pneumatic tent for all kinds of operations.

Vetter universal tents were developed especially for fire brigades. The tents are designed to need especially little time and personnel for transport, setup and takedown.

### Benefit from these features of our tents:

- self-erecting support frame
- low weight,
- small folded size
- ease of use

With our pneumatic tents, you can quickly set up protective space for colleagues or injured persons. Use the velcro fasteners to connect tents quickly and easily to other tents or directly with containers.

Vetter universal tents are suited to a wide variety of uses such as living quarters for large-scale operations, triage facilities, or decontamination measures. For the latter, you can add Vetter shower units to all our tents.

### Your pneumatic tent for quick operations:

- Only 2 people needed for setup, ready for use in less than three minutes
- Flexible, mobile and easy to use
- Long time of use independent of electricity
- One-piece system in a single package - no loose parts

**For optimum performance in the field, Vetter tents are equipped with extensive features - even in the basic version.**

## Emergency Pneumatics

### Technical data

- Working pressure: 0.5 bar (7.25 psi)
- Test pressure: 0.65 bar (9.4 psi)

Product	Art. no.	Setup time, approx. sec / sec	Ext. dimensions (L x W x H) m / ft.	Int. dimensions (L x W x H) m / ft.	Air requirement, at working pressure litres / cu.ft.	Folded size (L x W x H) cm / inch	Weight, approx. kg / lbs	Connectable with Product / Product	Win Quar Que
<b>PZ 12</b>	1520002901	40 40	3,7 x 3,86 x 2,58 11,8 x 12,4 x 8,3	3,7 x 3,5 x 2,4 11,8 x 11,2 x 7,7	1632 57,6	110 x 85 x 40 43 x 33 x 16	55 121	PZ 12 PZ 12	
<b>PZ 17</b>	1520000401	50 50	4,9 x 3,86 x 2,48 15,7 x 12,4 x 7,9	4,9 x 3,5 x 2,3 15,7 x 11,2 x 7,4	2025 71,5	110 x 85 x 60 43 x 33 x 24	65 143	PZ 17 / PZ 20 Decon PZ 17 / PZ 20 Decon	
<b>PZ 20</b>	1520004701	55 55	5 x 4,36 x 2,48 16 x 14 x 7,9	5 x 4 x 2,3 16 x 12,8 x 7,4	2332 82,3	110 x 85 x 60 43 x 33 x 24	75 165	PZ 20 PZ 20	
<b>PZ 25</b>	1520008901	120 120	5 x 5,36 x 2,58 16 x 17,2 x 8,3	5 x 5 x 2,4 16 x 16 x 7,7	2568 90,7	110 x 85 x 60 43 x 33 x 24	85 187	PZ 25 PZ 25	
<b>PZ 30</b>	1520009402	130 130	6 x 5,5 x 3,1 19,2 x 17,6 x 9,9	6 x 5,14 x 2,9 19,2 x 16,4 x 9,3	2866 101,2	110 x 85 x 60 43 x 33 x 24	104 229	PZ 30 / PZ 40 / PZ 40 3 L PZ 30 / PZ 40 / PZ 40 3 L	
<b>PZ 40</b>	1520010602	150 150	8 x 5,5 x 3,1 25,6 x 17,6 x 9,9	8 x 5,14 x 2,9 25,6 x 16,4 x 9,3	4060 143,3	110 x 85 x 85 43 x 33 x 33	117 258	PZ 30 / PZ 40 / PZ 40 3 L PZ 30 / PZ 40 / PZ 40 3 L	

### Accessories

- Inflation with cylinder
- Inflation with blower
- Deflation
- Equipment
- Lighting
- Climate control
- Water supply



#### In operation...

- Operation centre
- Weatherproof changing tent
- Crew or mess tent for large- scale operations
- Triage facility



#### Good reasons...

- Multifunction inflation connection for use with compressed air cylinder or blower
- Remains operational for several days without additional air
- Patented securing net in roof area optionally available



#### Guaranteed quality:

- Individually tested (with inspection seal)
- Integrated safety valve prevents overinflation
- High- quality, durable support frame
- Mould- and flame- resistant PU- cover material (DIN 4102 B1)

---

**Please contact us directly should you have any further questions concerning this product.**

Sales  
Phone.: +49 (0) 22 52 / 30 08-0  
Fax: +49 (0) 22 52 / 30 08-590  
E- Mail: [vetter.info@idexcorp.com](mailto:vetter.info@idexcorp.com)

**Or find the nearest dealer under:**  
[www.vetter.de/ support/ haendler](http://www.vetter.de/support/haendler)

---